



ARMY PUBLIC SCHOOL LALGARH JATTAN

TENDER INVITATION NOTICE



1. On behalf of Army Public School (APS) Lalgarh Jattan, sealed tenders are invited from reputed, Experienced and reliable firms/vendors for Installation of CCTV Surveillance System in Army Public School Lalgarh Jattan. The tender will be submitted under Two Bid System, i.e. Technical Bid and Financial Bid, in two separate sealed envelopes, duly superscribed as: "Tender for Installation of CCTV Cameras – APS Lalgarh Jattan"

Ser No	Description																																																																																																										
1.1	<p>Installation of CCTV cameras for Army Public School Lalgarh Jattan</p> <p>4MP IP Cameras – 55 Rack – 02 NVRs – 02 (Minimum 32 Channel Each) PoE Switch – As per the requirements Wire Bundle – As per the requirements Hard Disk – 02 (Minimum 4 TB Each)</p>																																																																																																										
1.2	<p>Technical Specification of all the above mentioned items –</p> <p>Cameras Specifications</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr><td>Image Sensor</td><td>1/2.9" 4MP PS CMOS Image Sensor</td></tr> <tr><td>Resolution</td><td>4 Megapixel (2688 × 1520)</td></tr> <tr><td>Lens</td><td>3.6 mm Fixed Lens</td></tr> <tr><td>IR Range</td><td>Up to 30 meters</td></tr> <tr><td>Day/Night</td><td>Auto (ICR) / Color / B/W</td></tr> <tr><td>Video Compression</td><td>H.265 / H.264</td></tr> <tr><td>Frame Rate</td><td>Up to 25/30 fps @ 4MP</td></tr> <tr><td>Noise Reduction</td><td>3D NR</td></tr> <tr><td>Power Supply</td><td>12V DC / PoE (802.3af)</td></tr> <tr><td>Casing</td><td>Metal Body</td></tr> <tr><td>Weather Proof</td><td>Suitable for indoor/outdoor use</td></tr> <tr><td>Ethernet</td><td>RJ-45 (10/100 Mbps)</td></tr> </table> <p>Rack Specifications</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr><td>Size of server rack</td><td>4U</td></tr> <tr><td>Basic Frame Material</td><td>CRC (MS Sheet)</td></tr> <tr><td>Construction</td><td>Welded Construction</td></tr> <tr><td>Front Door</td><td>Plain front door with key lock and gasket</td></tr> <tr><td>Mounting Type</td><td>Wall / Pole mounting with brackets</td></tr> <tr><td>Width</td><td>upto 550 mm</td></tr> <tr><td>Depth</td><td>upto 400 mm</td></tr> <tr><td>Height</td><td>upto 240 mm</td></tr> </table> <p>NVR 32 Channel Specifications</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr><td>Type</td><td>Network Video Recorder (NVR)</td></tr> <tr><td>Channels</td><td>32 Channel IP Camera Support</td></tr> <tr><td>Max Camera Resolution</td><td>Up to 4MP per Channel</td></tr> <tr><td>Video Compression</td><td>H.265 / H.264</td></tr> <tr><td>Video Output</td><td>HDMI & VGA</td></tr> <tr><td>Display Resolution</td><td>Up to 4K (HDMI)</td></tr> <tr><td>Hard Disk Support</td><td>2 × SATA HDD, Up to 10 TB per HDD</td></tr> <tr><td>Recording Modes</td><td>Manual / Schedule / Motion Detection</td></tr> <tr><td>Playback & Search</td><td>Date/Time & Event Based</td></tr> <tr><td>Backup</td><td>USB / Network</td></tr> <tr><td>Ethernet</td><td>1 × RJ-45 (10/100/1000 Mbps)</td></tr> <tr><td>Mobile Viewing</td><td>Android & iOS Support</td></tr> <tr><td>Alarm & Motion Detection</td><td>Supported</td></tr> <tr><td>Power Supply</td><td>AC 100–240V, 50/60Hz</td></tr> <tr><td>Power Consumption</td><td>< 35W (without HDD)</td></tr> </table> <p>PoE Switch Specifications</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr><td>Type</td><td>PoE Ethernet Switch</td></tr> <tr><td>Ports</td><td>8 × PoE Ports (RJ-45, 10/100 Mbps) 2 × Uplink Port (RJ-45)</td></tr> <tr><td>PoE Standard</td><td>IEEE 802.3af / at / bt</td></tr> <tr><td>PoE Power Output</td><td>Up to 30W per port (PoE) Up to 60W on high-power ports</td></tr> <tr><td>Total PoE Power Budget</td><td>120W</td></tr> <tr><td>Transmission Distance</td><td>Up to 250 m (extended mode) Up to 100 m (standard mode)</td></tr> <tr><td>Switching Capacity</td><td>2.0 Gbps</td></tr> <tr><td>Protection</td><td>Lightning & ESD Protection</td></tr> </table> <p>Wire Bundle</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr><td>Type</td><td>LAN Cable (For CCTV / Network Use)</td></tr> <tr><td>Conductor Material</td><td>CCA</td></tr> <tr><td>Conductor Size</td><td>0.50 mm</td></tr> <tr><td>Insulation Material</td><td>HDPE</td></tr> <tr><td>Jacket Material</td><td>PVC (Black/Grey)</td></tr> <tr><td>Cable Construction</td><td>4 Pair Twisted Cable</td></tr> <tr><td>Outer Diameter</td><td>Approx. 6.6 mm</td></tr> <tr><td>Length per Box</td><td>305 meters</td></tr> <tr><td>Rip Cord</td><td>Nylon</td></tr> <tr><td>Suitable For</td><td>PoE & IP Camera Cabling</td></tr> </table>	Image Sensor	1/2.9" 4MP PS CMOS Image Sensor	Resolution	4 Megapixel (2688 × 1520)	Lens	3.6 mm Fixed Lens	IR Range	Up to 30 meters	Day/Night	Auto (ICR) / Color / B/W	Video Compression	H.265 / H.264	Frame Rate	Up to 25/30 fps @ 4MP	Noise Reduction	3D NR	Power Supply	12V DC / PoE (802.3af)	Casing	Metal Body	Weather Proof	Suitable for indoor/outdoor use	Ethernet	RJ-45 (10/100 Mbps)	Size of server rack	4U	Basic Frame Material	CRC (MS Sheet)	Construction	Welded Construction	Front Door	Plain front door with key lock and gasket	Mounting Type	Wall / Pole mounting with brackets	Width	upto 550 mm	Depth	upto 400 mm	Height	upto 240 mm	Type	Network Video Recorder (NVR)	Channels	32 Channel IP Camera Support	Max Camera Resolution	Up to 4MP per Channel	Video Compression	H.265 / H.264	Video Output	HDMI & VGA	Display Resolution	Up to 4K (HDMI)	Hard Disk Support	2 × SATA HDD, Up to 10 TB per HDD	Recording Modes	Manual / Schedule / Motion Detection	Playback & Search	Date/Time & Event Based	Backup	USB / Network	Ethernet	1 × RJ-45 (10/100/1000 Mbps)	Mobile Viewing	Android & iOS Support	Alarm & Motion Detection	Supported	Power Supply	AC 100–240V, 50/60Hz	Power Consumption	< 35W (without HDD)	Type	PoE Ethernet Switch	Ports	8 × PoE Ports (RJ-45, 10/100 Mbps) 2 × Uplink Port (RJ-45)	PoE Standard	IEEE 802.3af / at / bt	PoE Power Output	Up to 30W per port (PoE) Up to 60W on high-power ports	Total PoE Power Budget	120W	Transmission Distance	Up to 250 m (extended mode) Up to 100 m (standard mode)	Switching Capacity	2.0 Gbps	Protection	Lightning & ESD Protection	Type	LAN Cable (For CCTV / Network Use)	Conductor Material	CCA	Conductor Size	0.50 mm	Insulation Material	HDPE	Jacket Material	PVC (Black/Grey)	Cable Construction	4 Pair Twisted Cable	Outer Diameter	Approx. 6.6 mm	Length per Box	305 meters	Rip Cord	Nylon	Suitable For	PoE & IP Camera Cabling
Image Sensor	1/2.9" 4MP PS CMOS Image Sensor																																																																																																										
Resolution	4 Megapixel (2688 × 1520)																																																																																																										
Lens	3.6 mm Fixed Lens																																																																																																										
IR Range	Up to 30 meters																																																																																																										
Day/Night	Auto (ICR) / Color / B/W																																																																																																										
Video Compression	H.265 / H.264																																																																																																										
Frame Rate	Up to 25/30 fps @ 4MP																																																																																																										
Noise Reduction	3D NR																																																																																																										
Power Supply	12V DC / PoE (802.3af)																																																																																																										
Casing	Metal Body																																																																																																										
Weather Proof	Suitable for indoor/outdoor use																																																																																																										
Ethernet	RJ-45 (10/100 Mbps)																																																																																																										
Size of server rack	4U																																																																																																										
Basic Frame Material	CRC (MS Sheet)																																																																																																										
Construction	Welded Construction																																																																																																										
Front Door	Plain front door with key lock and gasket																																																																																																										
Mounting Type	Wall / Pole mounting with brackets																																																																																																										
Width	upto 550 mm																																																																																																										
Depth	upto 400 mm																																																																																																										
Height	upto 240 mm																																																																																																										
Type	Network Video Recorder (NVR)																																																																																																										
Channels	32 Channel IP Camera Support																																																																																																										
Max Camera Resolution	Up to 4MP per Channel																																																																																																										
Video Compression	H.265 / H.264																																																																																																										
Video Output	HDMI & VGA																																																																																																										
Display Resolution	Up to 4K (HDMI)																																																																																																										
Hard Disk Support	2 × SATA HDD, Up to 10 TB per HDD																																																																																																										
Recording Modes	Manual / Schedule / Motion Detection																																																																																																										
Playback & Search	Date/Time & Event Based																																																																																																										
Backup	USB / Network																																																																																																										
Ethernet	1 × RJ-45 (10/100/1000 Mbps)																																																																																																										
Mobile Viewing	Android & iOS Support																																																																																																										
Alarm & Motion Detection	Supported																																																																																																										
Power Supply	AC 100–240V, 50/60Hz																																																																																																										
Power Consumption	< 35W (without HDD)																																																																																																										
Type	PoE Ethernet Switch																																																																																																										
Ports	8 × PoE Ports (RJ-45, 10/100 Mbps) 2 × Uplink Port (RJ-45)																																																																																																										
PoE Standard	IEEE 802.3af / at / bt																																																																																																										
PoE Power Output	Up to 30W per port (PoE) Up to 60W on high-power ports																																																																																																										
Total PoE Power Budget	120W																																																																																																										
Transmission Distance	Up to 250 m (extended mode) Up to 100 m (standard mode)																																																																																																										
Switching Capacity	2.0 Gbps																																																																																																										
Protection	Lightning & ESD Protection																																																																																																										
Type	LAN Cable (For CCTV / Network Use)																																																																																																										
Conductor Material	CCA																																																																																																										
Conductor Size	0.50 mm																																																																																																										
Insulation Material	HDPE																																																																																																										
Jacket Material	PVC (Black/Grey)																																																																																																										
Cable Construction	4 Pair Twisted Cable																																																																																																										
Outer Diameter	Approx. 6.6 mm																																																																																																										
Length per Box	305 meters																																																																																																										
Rip Cord	Nylon																																																																																																										
Suitable For	PoE & IP Camera Cabling																																																																																																										

1.2 **Technical Specification of all the above mentioned items –**

Hard Disk (4 TB) Specifications

Type	Internal Hard Disk Drive (HDD)
Capacity	4 TB
Form Factor	3.5 inch
Disk Type	Mechanical HDD
Rotation Speed	5400 RPM
Interface	SATA (Suitable for NVR)
Application	CCTV / NVR Recording

Important Instructions

2. **Cameras of any reputed and reliable brand** may be quoted, ensuring long-term serviceability, availability of spares and after-sales support.
 3. Interested firms/dealers to forward the quotations along with details name of firm GST & TIN Number, permanent postal address, Mobile No and business profile.
 4. Technical literature of the items will also be provided by the dealers/vendors.
 5. Vendors must submit : **One Technical Bid and One Financial Bid in separate sealed envelopes.**
 6. The **quoted rates must be inclusive of** GST, Installation charges, Labour charges, Cabling, fixing, configuration, testing & commissioning, Any other incidental cost. **No extra charges will be paid later.**
 7. Financial Bid of only those vendors whose Technical Bid is found acceptable will be opened.
 8. Vendors are **strongly advised to visit the school premises** to assess - Exact camera locations, Scope of work, and Site conditions before submitting their quotation.
 9. All items quoted/supplied by the vendor including **Cameras, NVR, HDD, PoE Switch, Cables, Connectors and all allied accessories** must carry a **minimum comprehensive warranty of Two (02) years** from the date of successful installation, testing and commissioning. The vendor shall be responsible for **repair/replacement of defective items during the warranty period at no extra cost** to the school.
 10. **Bids can be accepted by speed post / registered post / couriers / e-mail or physical drop in two separate bids (i.e. Technical and Financial) in separate envelopes by 05 Feb 2026 till 1400hrs. 01 x Box will be kept at TCP-2 for submission of the bids.**
- Note :-**
- (a) Tenders without GST/TIN shall be rejected.
 - (b) SAMC reserves the right to reject or accept any tender without any reason thereof.
 - (c) SAMC also has the right to cancel any procurement / work.
 - (d) Tender bids must be sent either through the registered post or drop in the quotation box personally at TCP-2, LGJ, MIL STN.
 - (e) The school will not be responsible for any postal delay.

Email id : apslalgargh@awesindia.edu.in
Mobile : 7230002908

PRINCIPAL